


Sequence Acoustic Baffles



- » Excellent acoustic absorption
- » Reinforced, factory finished edges
- » Simple suspension system
- » Durable mineral wool core
- » Lightweight, easy to handle panels
- » Good humidity resistance

SOFT FIBRE

+44 (0)1455 618 787
enquiries@burgesscep.com
Brookfield Road, Hinckley LE10 2LL
Verulam Road, Stafford ST16 3EA

WWW.BURGESSCEP.COM

Sequence Acoustique Baffles




The Sequence Acoustique Baffles range offers stunning visual options with individually suspended vertical panels up to 2400mm. These offer outstanding acoustic absorption, yet enable air to circulate around them.

Panels can be hung in rows or patterns to create a range of aesthetics. The reinforced mineral wool core and factory finished face and edges produce a strong, durable product that requires very little maintenance.

Available in white as standard, with the option to match any RAL colour, as well as a selection of fabric wrapped panels. Non-standard sizing also available, please contact our technical team for details.

BAFFLES



1200 x 300mm	cartons of 10 baffles	G3001-WG-10
1200 x 600mm	cartons of 5 baffles	G3000-WG-05

Suspended using 2 baffle hangers (S1922-SC) or 2 hanging kits (S1924-HK).



SOUND ABSORPTION

Class A in accordance with EN ISO 11654. α_w : 1.00 in accordance with EN ISO 11654. Noise Reduction Coefficient (NRC): 0.90 in accordance with ASTM C 423-01.



PRODUCT WEIGHT

These tiles weigh approximately 5kg per m².



CLEANING & HYGIENE

These tiles can be easily cleaned. Contact us for cleaning guidelines.



TILE LOADING

These tiles are not designed to support the weight of any services. Please contact us for grid loading data.



ACCESSIBILITY

These panels are individually suspended and demountable.



FIRE PERFORMANCE

Euroclass A2-s1, d0 in accordance with EN 13501-1.



HUMIDITY RESISTANCE

Suitable in conditions up to 100% relative humidity at 30°C.