



Sequence Sport Wall Panels



- » Enhanced impact resistance
- » Excellent acoustic absorption
- » White painted or fabric covered panels
- » Simple framing system
- » Durable mineral wool core
- » Lightweight, easy to handle panels
- » Good humidity resistance
- » Available in four standard colours

SOFT FIBRE

- +44 (0)1455 618 78
- enquiries@burgesscep.com
- · Brookfield Road, Hinckley LE10 2LL
- Verulam Road, Stafford ST16 3EA

NWW.BURGESSCEP.COM

Sequence Sport Wall Panels

The Sequence range of wall panels offer outstanding acoustic absorption and excellent design options. The panel themselves are 40mm thick resin bonded mineral wool and they can be covered with either a contemporary white painted finish or a number of different durable colour fabric finishes.

The panels slot into either a steel or aluminium framing system, in either a black or white polyester powder coated finish. Panels can be cut and shaped to suit almost any design, offering unlimited aesthetic options.



SEQUENCE



2700 x600 x 40mm cartons of 4 panels G2000

Non-standard sizing also available, please contact our technical team for details.

Available in CEP White, Blue, Grey and Black finish to face.



SOUND ABSORPTION

Class A in accordance with EN ISO 11654. ∂ w: 1.00 in accordance with EN ISO 11654. Noise Reduction Coefficient (NRC): 0.90 in accordance with ASTM C 423-01.



FIRE PERFORMANCE

Wall panel core rated to Euroclass A2s1, d0 in accordance with EN 13501-1



PRODUCT WEIGHT

These tiles weigh approximately 2kg per m².



ACCESSIBILITY

These tiles are easily demounted.



TILE LOADING

These tiles are not designed to support the weight of any services. Please contact us for grid loading data.



HUMIDITY RESISTANCE

Suitable in conditions up to 95% relative humidity at 30°C.