

RHINO-HS

LPS1175 Rated Hinged Doors



Rhino Doors
THE STRENGTH TO PROTECT

Rhino-HS LPS1175 SR3&4 security rated hinged doors

Designed to resist attacks from deliberate forced entry using bodily force and a wide selection of attack options.

Tested to: UK security standard
LPS1175 Issue 7 to levels SR3 & SR4
European fire standard BS EN1634-1 to integrity level E240

Configurations: Single and double leaf, single swing with optional over panels

Maximum security certified openings:
Single leaf 1500x2920mm
Double leaf 2858x2920mm
Single with over panel 1500x4000mm
Double with over panel 2858x4000mm
(w x h)

Leaf: 66mm thick with 3mm thick galvanized steel skins, an insulated core and vertical & horizontal internal stiffeners

Frame: 90x50x3mm steel box section Mitred and butt welded and filled with insulation material, and a welded steel box section stop

Ironmongery: Dorma TS83 overhead closer
Mico 942 3-point latch with top and bottom acting shoot bolts. Available with optional single point locks
Mico HD handle with CHSR3 lock guard
Top and bottom surface mounted shoot bolts to retain the inactive on double doors

Finish: Wet film or Polyester powder coated in any RAL or BS colour

Suitable Substrate: To be mechanically anchored directly to structural steel or masonry substrates



Rhino-HS Double Leaf



Rhino-HS Single Leaf



Contact Details

Rhino Systems Ltd

Maritime Road
Llewellyns Quay
Port Talbot
SA13 1RF

T: +44 (0)1639 888 119

F: +44 (0)1639 898 119

enquiries@rhinodoors.com

www.rhinodoors.com



'A portfolio company of Cyrus Investment Management LLP'