

RHINO-RS

LPS1175 Rated Security Shutters



Rhino Doors

THE STRENGTH TO PROTECT

Rhino-RS LPS1175 SR4&5 rated security shutters

Designed to resist attacks from deliberate forced entry using bodily force and a wide selection of attack options.

| | |
|---------------------|---|
| Tested to: | UK standard LPS1175 Issue 7 to Level SR4&5 |
| Arrangement: | Vertical shutters, with roller shutter boxes mounted at high level. |
| Shutter Curtain: | MaxiDUO lath profile to high strength aluminium, grade 6063 T6 |
| Frame/Guides: | Heavy duty guide profiles to grade 6063 T6, with composite material seal |
| Bottom Rail: | Reinforced bottom rail to grade 6063 T6 |
| Maximum Size: | 6000 x 6000mm |
| Operation: | Motorised to allow controlled ascent and descent. Shutter to automatically lock into position upon descent without manual intervention or key locking |
| Suitable Substrate: | To be mechanically anchored directly to structural steel or masonry substrate as certified to LPS 1175 Level 4 & 5, Issue 7 |
| Ironmongery: | As agreed with manufacturer |
| Finish: | Polyester powder coated to 25 microns in Standard RAL and BS colours |



Contact Details

Rhino Systems Ltd

Maritime Road
Llewellyns Quay
Port Talbot
SA13 1RF

T: +44 (0)1639 888 119

F: +44 (0)1639 898 119

enquiries@rhinodoors.com

www.rhinodoors.com



'A portfolio company of Cyrus Investment Management LLP'