


GREEN ENERGY



legg-GS65A10



legg-2TGS65A10



legg-3TGS65A10

Description

Housing - Die cast aluminium powder coated with choice of RAL colors.

Diffuser - Tempered glass diffuser.

Reflector - Aluminium lamp reflector.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).

Objective



Since downlight has the advantage of light adjustment they can be installed easily around the edge of the room to get that clean and streamlined light for the perfect ambience. Perfect for areas which required bright light and energy saving consumption at the same time. Completely dustproof. Protected against splash of water.

Obbiettivo

Poiché il downlight ha il vantaggio della regolazione della luce, è possibile installarlo facilmente lungo il bordo della stanza per ottenere una luce pulita e aerodinamica per l'ambiente perfetto. Perfetto per le aree che richiedevano luce intensa e consumo energetico allo stesso tempo. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.

Directional

CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
legg-GS65A10	1*10W	44-54	15°/24°/40°	110 lm/W	120 x 120 x 85mm ☞ 100*100mm
legg-2GS65A210	2*10W	44-54	15°/24°/40°	110 lm/W	210 x 120 x 82mm ☞ 190*107mm
legg-3GS65A310	3*10W	44-54	15°/24°/40°	110 lm/W	312 x 130 x 84mm ☞ 285*117mm



- 2700K
- 3000K
- 4000K
- 5000K



CRI >90

-20° C
55° C

85~265V
50/60Hz

