



legg-JD35302



legg-JD35302



legg-JD35302

**Objective**

Since downlight has the advantage of light adjustment they can be installed easily around the edge of the room to get that clean and streamlined light for the perfect ambience. Perfect for areas which required bright light and energy saving consumption at the same time. Completely dustproof. Protected against splash of water.

**Obiettivo**

Poiché il downlight ha il vantaggio della regolazione della luce, è possibile installarlo facilmente lungo il bordo della stanza per ottenere una luce pulita e aerodinamica per l'ambiente perfetto. Perfetto per le aree che richiedevano luce intensa e consumo energetico allo stesso tempo. Protetto contro la penetrazione di corpi solidi. Protetto contro gli spruzzi d'acqua.

**Description**

**Housing** - Die cast aluminium powder coated with choice of RAL colors.


**Diffuser**- Tempered glass lens diffuser.

**Standards** - Manufactured in accordance with IEC 60598.


**LED** - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).

CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
------	-------	----	------------	--------	-----------


legg-A06217	1*7W	44	15°/24°/36°	110 lm/W	130 x 130 x 128mm 110x110mm
legg-A06227	2*7W	44	15°/24°/36°	110 lm/W	235 x 130 x 128mm 215x110mm
legg-A06237	3*7W	44	15°/24°/36°	110 lm/W	130 x 130 x 128mm 315x110mm



110x110mm



235x130mm





315x110mm

Color Options



Beam Angle



- 2700K
- 3000K
- 4000K
- 5000K



CRI >90

-20° C  
55° C

85~265V  
50/60Hz

