

GREEN ENERGY



legg-H9939

**Description**

**Housing** - Die cast aluminium powder coated with choice of RAL colors.

**Diffuser** - Tempered glass diffuser.

**Reflector** - Aluminium lamp reflector.

**Standards** - Manufactured and tested as per PTPS IEC 62722.

**LED** - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).

**Objective**

Eco friendly surface downlight yet will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption. Completely dustproof. Protected against high pressure water jets.


**Obiettivo**

Il downlight di superficie eco-compatibile ti garantirà comunque che questo prodotto è durevole e durerà a lungo. Dal momento che questa è una luce a LED, questo sicuramente ti farà risparmiare da un costoso consumo di energia. Si prevede di fornire ottimi risultati con un consumo minimo.



Completamente antipolvere. Protetto contro i getti d'acqua ad alta pressione.



CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
legg-H993920	1*20W	65	15°/24°/36°	110 lm/W	150 x 150 x140mm
legg-H993930	1*30W	65	15°/24°/36°	110 lm/W	150 x 150 x200mm
legg-H993945	1*45W	65	15°/24°/36°	110 lm/W	150 x 150 x300mm



Color Options



- 2700K
- 3000K
- 4000K
- 5000K



CRI >90

-20° C  
55° C

85~265V  
50/60Hz

