



legg-KD11

**Description**

**Housing** - Die cast aluminium powder coated with choice of RAL colors.

**Diffuser** - Tempered glass diffuser.

**Reflector** - Aluminium reflector.

**Standards** - Manufactured and tested as per PTSP IEC 62722.

**LED** - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).

**Objective**

Eco friendly surface downlight yet will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption.

Completely dustproof.

Protected against splash of water.


**Obiettivo**

Il downlight di superficie eco-compatibile ti garantirà comunque che questo prodotto è durevole e durerà a lungo. Dal momento che questa è una luce a LED, questo sicuramente ti farà risparmiare da un costoso consumo di energia. Si prevede di fornire ottimi risultati con un consumo minimo.


Completamente antipolvere.

Protetto contro gli spruzzi d'acqua.

CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
legg-KD11	6W, 8W, 12W	54	24°	110 lm/W	90 x 130mm



Beam Angle



- 2700K
- 3000K
- 4000K
- 5000K

Color Options



CRI >90

-20° C  
55° C

85~265V  
50/60Hz

Leggero  
PHILIPS Drivers

LED Chips  
BRIDGELUX  
CREE

