



legg-C68017

**Description**

**Housing** - Die cast aluminium powder coated with choice of RAL colors.

**Diffuser** - Tempered glass diffuser.

**Reflector** - Aluminium reflector.

**Standards** - Manufactured and tested as per PTSP IEC 62722.

**LED** - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).

**Objective**


Providing a projector like light is the primary characteristics of this tracklight. As this is an LED based light it will surely produces high quality and efficient performance light. Works perfectly in accordance of LED energy saving. Protected against the penetration by solid bodies. Protected against sprays of water.

**Obiettivo**



Fornire un proiettore come la luce è la caratteristica principale di questo proiettore. Poiché si tratta di una luce a LED, produrrà sicuramente luce ad alte prestazioni ed efficienza. Works perfectly in accordance of LED energy saving. Protetto contro la penetrazione di corpi solidi. Protetto contro gli spruzzi d'acqua.




CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
legg-C68017	7W	44	15°/24°/36°	110 lm/W	68 x 100mm



Color Options



MEGAMAN GU10 PAR16  
7W 2800K 24D Max.2200cd



- 2700K
- 3000K
- 4000K
- 5000K



CRI >90

-20° C  
55° C

85~265V  
50/60Hz

Leggero  
PHILIPS Drivers

BRIDGELUX  
LED Chips  
CREE

