

GREEN ENERGY



DOWNLIGHT

Perfect for work lighting especially in places where a lot of nice and bright light is required. Since downlight has the advantage of light adjustment they can be installed around the edge of the room to get that clean and streamlined light for that perfect ambience. Completely dustproof. Protected against jets of water.

Description

Housing

Die cast aluminium

Diffuser



Tempered glass

Reflector

Anodized aluminium reflector

LED-50,000 Hrs Life span

CODE	POWER	IP	BEAM ANGEL	LUMENS	DIMENSION
legg-CR0954	9W	54-65	15°/20°/38°	110 lm/W	92mm x 62mm Φ82mm
legg-CR1654	16W	54-65	15°/20°/38°	110 lm/W	136mm x 75mm Φ120mm
legg-CR2454	24W	54-65	15°/20°/38°	110 lm/W	175mm x 100mm Φ155mm
legg-CR3254	32W	54-65	15°/20°/38°	110 lm/W	196mm x 105mm Φ172mm
legg-CR4554	45W	54-65	15°/20°/38°	110 lm/W	230mm x 125mm Φ210mm



- 2700K
- 3000K
- 4000K
- 5000K



CRI >90

-20° C
55° C

85~265V
50/60Hz

Leggero
PHILIPS Drivers

LED Chips
BRIDGELUX
CREE

