



legg-JD7060B5



legg-JD7060G5



legg-JD7060W5

Description

Housing - Die cast aluminium powder coated with choice of RAL colors.

Diffuser - Frosted glass diffuser.

Reflector - Aluminium reflector.

Standards - Manufactured in accordance with IEC 60598.

LED - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).

Objective

Light designed to direct a narrow intense beam of light at different distances in small area. Illuminating them properly by establishing the focal ratios best suited to each situation. Usually used in Living, Hallway, Bathroom and Etc. Completely dustproof. Protected against splash of water.


Obiettivo

Luce progettata per dirigere uno stretto intenso fascio di luce a diverse distanze in piccola area. Illuminandoli correttamente stabilendo i rapporti focali migliori adatto a ogni situazione. Solitamente usato in soggiorno, corridoio, bagno ed ecc. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.





CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
------	-------	----	------------	--------	-----------

legg-JD7060B5	5W	54	20°	110 lm/W	70 x 90mm Φ60mm
legg-JD7060G5	5W	54	20°	110 lm/W	70 x 90mm Φ60mm
legg-JD7060W5	5W	54	20°	110 lm/W	70 x 90mm Φ60mm



Color Options



- 2700K
- 3000K
- 4000K
- 5000K



CRI >90

-20° C
55° C

85~265V
50/60Hz

Leggero
PHILIPS

BRIDGELUX
LED Chips
CREE

