

GREEN ENERGY



legg-JD1860A7

Description

Housing - Die cast aluminium powder coated with choice of RAL colors.

Diffuser - Tempered glass diffuser.

Reflector - Aluminium reflector.

Standards - Manufactured in accordance with IEC 60598.

LED - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).

Objective


Light designed to direct a narrow intense beam of light at different distances in small area. Illuminating them properly by establishing the focal ratios best suited to each situation. Usually used in Living, Hallway, Bathroom and Etc. Protected against the penetration by solid bodies. Protected against sprays of water.

Obiettivo



Luce progettata per dirigere uno stretto intenso fascio di luce a diverse distanze in piccola area. Illuminandoli correttamente stabilendo i rapporti focali migliori adatto a ogni situazione. Solitamente usato in soggiorno, corridoio, bagno ed ecc. Protetto contro la penetrazione di corpi solidi. Protetto contro gli spruzzi d'acqua.



CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
legg-JD1860A7	7W	44	18°/24°/38°	110 lm/W	70 x 60mm Φ60mm



Color Options



- 2700K
- 3000K
- 4000K
- 5000K



CRI >90

-20° C
55° C

85~265V
50/60Hz

