



legg-A1431



legg-A0693

Objective

Perfect for work lighting especially in places where a lot of nice and bright light is required. Since downlight has the advantage of light adjustment they can be installed around the edge of the room to get that clean and streamlined light for that perfect ambience. Completely dustproof. Protected against high pressure water jets.

Obiettivo

Perfetto per l'illuminazione di lavoro soprattutto in luoghi dove molto bello e luminoso è richiesta luce. Dal momento che il downlight ha il vantaggio della regolazione della luce loro può essere installato facilmente lungo il bordo del spazio per ottenere quello pulito e aerodinamico luce per l'atmosfera perfetta. Completamente antipolvere. Protetto contro i getti d'acqua ad alta pressione. Completamente antipolvere. Protetto contro i getti d'acqua ad alta pressione.

Description

Housing - Die cast aluminium powder coated with choice of RAL colors.

Diffuser - Tempered glass diffuser.


Reflector - Aluminium reflector.

Standards - Manufactured in accordance with IEC 60598.



LED - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).



CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
legg-A143120	20W	65	15°/24°/36°/75°	110 lm/W	278 x 195mm ⌀250mm
legg-A143130	30W	65	15°/24°/36°/75°	110 lm/W	278 x 195mm ⌀250mm
legg-A143145	45W	65	15°/24°/36°/75°	110 lm/W	278 x 195mm ⌀250mm
legg-A069345	45W	65	15°/24°/36°	110 lm/W	240 x 240mm ⌀222mm



Color Options



- 2700K
- 3000K
- 4000K
- 5000K



CRI >90

-20° C
55° C

85~265V
50/60Hz

Leggero
PHILIPS Drivers

LED CHIPS
BRIDGELUX
CREE

