

T8000 Series

T8000 Touch Screen Thermostat



T8000 Series Touch Screen Thermostat

Application

T8200···JS0/R0 Touch screen thermostats are designed to control heating, cooling, or year round air conditioning unit in Commercial, Industrial and Residential Installation. Typical applications include the control of fan coil units, packaged terminal air conditioners and combination of heating and cooling equipment. As part of the system, T8000 controls a two-way or three-way valve and a multi-speed line voltage fan.

T8200···JF0 Touch screen thermostat is applicable to the two-in-one system of central air-conditioner and floor heating. In summer, comfortable environment is reached by controlling the fan coil of air conditioning system with local temperature. In winter, both warm air from air-conditioner and floor heating are available for quick heating.

T8000 features with microcomputer control, large LCD screen display, and displays the status of work mode (cooling/floor heating/heating/floor heating&heating/air venting), fan speed, indoor temperature and set temperature etc.. Capacitance touch screen enhances the fluency on operation. Keypad includes: Power on/off (⏻), Mode selection (M), Fan Speed selection (⚙️), Clock/Timer (🕒) and two Adjustment buttons (⬆️&⬆️).



Features and Benefits

Touch screen	<ul style="list-style-type: none"> • Capacitance touch screen enhances the fluency on operation
Backlit Liquid Crystal Display (LCD)	<ul style="list-style-type: none"> • Offer Easy-to-Read Real-time control status of the environment, graphical messages with constant backlight that brightens during user interaction
6 Function Keys	<ul style="list-style-type: none"> • All-in-One location function keys, simplified user to change the setpoint and parameter
	<ul style="list-style-type: none"> • Molded Industrial Standard Graphical Symbol
Appearance	<ul style="list-style-type: none"> • Attractively-Style Twin-Ring Streamline ABS Plastic Cover and Base
	<ul style="list-style-type: none"> • All-in-One Enclosure Design without Protrusion of Power Circuit
Energy Saving	<ul style="list-style-type: none"> • Features with Unoccupied Function
	<ul style="list-style-type: none"> • Requires no batteries; EEPROM retains the last events and parameter settings after a loss of power
Installation, Service and Maintenance	<ul style="list-style-type: none"> • Universal Mounting with Standard Wall Box
	<ul style="list-style-type: none"> • Quick Replacement to reduce to Downtime of Service Maintenance

Function

Item	Description	T8200-TB20-9JRO	T8200-TB20-9JSO	T8200-TF20-9JRO	T8200-TF20-9JSO	T8200-TB21-9JRO	T8200-TB21-9JSO	T8200-TB20-9JF0
Application	2-pipe heating or cooling	■	■					
	4-pipe heating and cooling			■	■			
	2-pipe modulating					■	■	
	2-pipe heating or cooling, Floor heating							■
User-interface	Touch Screen	■	■	■	■	■	■	■
	Backlight (White)	■	■	■	■	■	■	■
	EN/Icon	■	■	■	■	■	■	■
	°C/°F Changeable	■	■	■	■	■	■	■
Energy Saving	Ventilation Mode	■	■	■	■	■	■	■
	Setpoint Limit	■	■	■	■	■	■	■
	Occupied contact with NO/NC options		■		■		■	
	Unoccupied setpoints		■		■		■	
	Low fan in unoccupancy		■		■		■	
	Auto Changeover			■	■			
Other Functions	Timer on/off	■	■	■	■	■	■	■
	Display setpoint only	■	■	■	■	■	■	■
	Anti-freezing	■	■	■	■	■	■	■
	Key Lock	■	■	■	■	■	■	■
	Display temperature calibration	■	■	■	■	■	■	■
	Remote temperature sensor	■		■		■		
	Restart after power failure	■	■	■	■	■	■	■
	Timer Function	■	■	■	■	■	■	■
Certificate	CE	■	■	■	■	■	■	■

Model Selection Guide

	T	8	2	0	0	-	T	B	2	0	-	9	J	S	0
Touch Screen	8	=	Touch Screen	8											
Version	2	=	Version	2											
System	0	=	ON/OFF	0											
Fan Control	0	=	Auto-Hi-Me-Lo		0										
Temperature Scale	T	=	°C or °F optional			T									
Application	B	=	2-pipe heating or cooling				B								
	F	=	4-pipe heating and cooling												
Reserve	2	=	Reserve					2							
Control	0	=	ON/OFF							0					
	1	=	Modulating												
Color	9	=	White								9				
Logo	J	=	JCI										J		
Function	S	=	For FCU (With unoccupied function)											S	
	R	=	For FCU (With remote sensor)												
	F	=	For FCU and Floor Heating												
Reserve	0	=	Reserve												0

Product Overview

T8000 touch screen thermostat with 7-basic models cover all types of FCU standalone applications, air conditioning and floor heating 2-in-1 application. There are models for 2-pipe cooling or heating, 4-pipe cooling and heating, air conditioning and floor heating, and for 2-wire valve control. On-board high accuracy NTC sensor allows precision comfort control over occupied space area.

The T8000 thermostats come with 12-hours timer that allows user to schedule On-Time or Off-Time for the fan coil depending on user needs.

88 x 88mm size allows for 75 x 75 x 35mm standard wall box installation.

Model T8200-TB20-9JSO

The Model T8200-TB20-9JSO is with AC220V, LCD display (with Backlit) fan coil unit thermostat that design for cooling or heating fan coil unit with 2-wire valve actuator application. Integrated with System On/Off button allows user to shutdown the T8000 and cutoff the output power for fan (cutoff the Output power for Valve Actuator). Simply pressing the fan speed button, allows user selection of Auto-High-Med-Low fan speed. All fan output by relay that can withstand max. of 5Amp (Res). operating current.

Additional Dry-contact for Occupancy mode that allows better comfort control and to achieve energy cost saving.

Model T8200-TB20-9JRO

The Model T8200-TB20-9JRO is with AC220V, LCD display (with Backlit) fan coil unit thermostat that design for cooling or heating fan coil unit with 2-wire valve actuator application. Integrated with System On/Off button allows user to shutdown the T8000 and cutoff the output power for fan (cutoff the Output power for Valve Actuator). Simply pressing the fan speed button, allows user selection of Auto-High-Med-Low fan speed. All fan output by relay that can withstand max. of 5Amp (Res). operating current.

With remote temperature sensor. While remote sensor is connected, the built-in sensor will be disable automatically.

Model T8200-TF20-9JSO

The Model T8200-TF20-9JSO is with AC220V, LCD display (with Backlit) fan coil unit thermostat that design for cooling or heating fan coil unit with 4-wire valve actuator application. Integrated with System On/Off button allows user to shutdown the T8000 and cutoff the output power for fan (cutoff the Output power for Valve Actuator). Simply pressing the fan speed button, allows user selection of Auto-High-Med-Low fan speed. All fan output by relay that can withstand max. of 5Amp (Res). operating current.

Additional Dry-contact for Occupancy mode that allows better comfort control and to achieve energy cost saving.

Model T8200-TF20-9JRO

The Model T8200-TF20-9JRO is with AC220V, LCD display (with Backlit) fan coil unit thermostat that design for cooling or heating fan coil unit with 4-wire valve actuator application. Integrated with System On/Off button allows user to shutdown the T8000 and cutoff the output power for fan (cutoff the Output power for Valve Actuator). Simply pressing the fan speed button, allows user selection of Auto-High-Med-Low fan speed. All fan output by relay that can withstand max. of 5Amp (Res). operating current.

With remote temperature sensor. While remote sensor is connected, the built-in sensor will be disable automatically.

Model T8200-TB21-9JSO

The Model T8200-TB21-9JSO is with AC24V, LCD display (with Backlit) fan coil unit thermostat that design for cooling or heating fan coil unit with modulating(0-10V) valve actuator application. Integrated with System On/Off button allows user to shutdown the T8000 and cutoff the output power for fan (cutoff the Output power for Valve Actuator). Simply pressing the fan speed button, allows user selection of Auto-High-Med-Low fan speed. All fan output by relay that can withstand max. of 5Amp (Res). operating current.

Additional Dry-contact for Occupancy mode that allows better comfort control and to achieve energy cost saving.

Model T8200-TB21-9JRO

The Model T8200-TB21-9JRO is with AC24V, LCD display (with Backlit) fan coil unit thermostat that design for cooling or heating fan coil unit with modulating(0-10V) valve actuator application. Integrated with System On/Off button allows user to shutdown the T8000 and cutoff the output power for fan (cutoff the Output power for Valve Actuator). Simply pressing the fan speed button, allows user selection of Auto-High-Med-Low fan speed. All fan output by relay that can withstand max. of 5Amp (Res). operating current.

With remote temperature sensor. While remote sensor is connected, the built-in sensor will be disable automatically.


Model T8200-TB20-9JFO

The Model T8200-TB20-9JFO is with AC220V, LCD display (with Backlit) thermostat that design for air conditioning and floor heating with 2-wire valve actuator application. Integrated with System On/Off button allows user to shutdown the T8000 and cutoff the output power for fan (cutoff the Output power for Valve Actuator). Simply pressing the fan speed button, allows user selection of Auto-High-Med-Low fan speed. All fan output by relay that can withstand max. of 5Amp (Res). operating current.


IMPORTANT:

Use this T8000 Series Line Voltage Thermostat only as an operating control. Where failure of malfunction of the T8000 Series Thermostat could lead to personal injury or property damage to the controlled equipment or other property, additional precautions must be designed into the system. Incorporate and maintain other devices such as supervisory or alarm systems or safety or limit controls intended to warn of, or protect against, failure or malfunction of the T8000 Series Thermostat.

Dimensions




T8200-TB21.../T8200-TF.../T8200-TB20-9JF0



T8200-TB20-9JS0/JR0

Installation


T8000 thermostats allow for 75 x 75 x 35mm standard wall box installation.




* Remove the insulating strip before installation

Wiring Diagram


T8200-TB20-9JR0




T8200-TB20-9JS0




T8200-TF20-9JR0




T8200-TF20-9JS0




T8200-TB21-9JR0



T8200-TB21-9JS0



T8200-TB20-9JF0



Ordering Information

To order the replacement T8000 Series thermostat, contact the nearest Johnson Controls® representative. Specify the desired product code number according to Table of "Function" and "Model Selection Guide".

"IMPORTANT: The power supply to the thermostat must include overload protection. Failure to include overload protection may result in damage to the thermostat.

Specifications

Product	T8000 Touch screen thermostat	
	T8200-TB20-9JR0	Backlit LCD 2-pipe Cooling / Heating FCU Thermostat with remote sensor
	T8200-TB20-9JS0	Backlit LCD 2-pipe Cooling / Heating FCU Thermostat and Occupancy Contact
	T8200-TF20-9JR0	Backlit LCD 4-pipe Cooling and Heating FCU Thermostat with remote sensor
	T8200-TF20-9JS0	Backlit LCD 4-pipe Cooling and Heating FCU Thermostat and Occupancy Contact
	T8200-TB21-9JR0	Backlit LCD 2-pipe Cooling / Heating FCU Thermostat (modulating) with remote sensor
	T8200-TB21-9JS0	Backlit LCD 2-pipe Cooling / Heating FCU Thermostat (modulating) and Occupancy Contact
	T8200-TB20-9JF0	Backlit LCD 2-pipe Cooling / Heating FCU and Flooring Heating Thermostat
Power Requirements	AC85-260V 50/60HZ (T8200-TB20.../T8200-TF...)	
	AC24V±10% 50/60HZ (T8200-TB21...)	
Accuracy	±1°C	
Display Range	0-55°C	
Setpoint Range	5-35°C	
Unoccupied Mode	T8200...9JS0 External Voltage-Free Contact Input Signal	
Remote sensor	T8200...9JR0 with remote temperature sensor NTC 10K, 1.5 m, Max.20m (0.7 ~1.0mm ²)	
Termination	Screw terminals	
Valve Control	T8200-TB20-9JR0 (2-pipe Cooling / Heating)	1 x Single-Pole, Single Throw (SPST), 5A(Maximum), Relay Output
	T8200-TB20-9JS0 (2-pipe Cooling / Heating)	1 x Single-Pole, Single Throw (SPST), 5A(Maximum), Relay Output
	T8200-TF20-9JR0 (4-pipe Cooling and Heating)	2 x Single-Pole, Single Throw (SPST), 5A(Maximum), Relay Output
	T8200-TF20-9JS0 (4-pipe Cooling and Heating)	2 x Single-Pole, Single Throw (SPST), 5A(Maximum), Relay Output
	T8200-TB21-9JS0 (2-pipe Cooling / Heating)	0-10V Output
	T8200-TB21-9JR0 (2-pipe Cooling / Heating)	0-10V Output
	T8200-TB20-9JF0 (2-pipe Cooling / Heating with floor heating)	2 x Single-Pole, Single Throw (SPST), 5A(Maximum), Relay Output
Fan Control	3 x Single-Pole, Single Throw (SPST) , 5A (Res.) at 250 VAC (Maximum); Relay Output for High-Med-Low Fan	
Ambient Operating Conditions	0 to 45°C 90% Non-condensing RH	
Ambient Storage Conditions	-10 to 60 °C 90% Non-condensing RH	
Housing Material	PC: UL 94-V0	
Protection Class	IP20	
Certification	CE	
Dimensions	88 x 88 mm	
Shipping Weight	Appr.214g	

* When connected, the On/Off switch does not disconnect power to the unit; it only turns off or on the LCD and functions.