

1G1BR1G

MANUAL TILT GAS BRATT PAN, S/S AISI 430 BOTTOM



RANGE FEATURES

- Top: 18-10 stainless steel (12/10 mm gauge)
- Free-standing structure with top, front panels, sides and control consoles in 18-10 stainless steel; back panels in stainless steel.
- Top, sides, back, front panels and control consoles with satin scotchbrite finish.
- Side-by-side top configurations with secure fixing between units.
- IPX5 protection rating on all units.
- CE approval of all gas products.



FUNCTIONAL FEATURES



- Cooking well with rounded corners, base and walls in 18-10 stainless steel thickness 20/10 mm, with polished interior; radiant well base in AISI 430 stainless steel thickness 10 mm
- Well dimensions (mm) 630 x 460 x 183 h. Available cooking surface 23.5 dm². Well capacity at drain level: 54 litres. Well capacity at recommended level: 40 litres.
- Specific output at well base for cooking: 510 W/dm².
- Well with outlet spout specially shaped to enable product drainage without overflowing.
- Lid mounted on spring-loaded hinges.
- Heating with multiple self-stabilising flame burner. Heating output controlled by power modulator linked to double threshold thermal sensor fitted in well base.
- Manual well tilting with handwheel operating through a lead screw mounted on front of appliance.
- Sealed exhaust flue with enamelled guard at back of appliance top.
- Heat-resistant knobs with screen printed markings and reference index printed on control console.
- Height adjustable floor-mounted feet in 18-10 stainless steel - floor clearance 180 mm, with non-scratch sole in insulating plastic material.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

TECHNICAL FEATURES

- Multiple flame burner controlled by pilot light and thermocouple with spark ignition. Temperature control with thermostat valve. Operating temperature: 100°C - 270 °C.
- Manual resetting safety thermostat.
- Easy access to all controls and parts from front of appliance.

Width	Cm	70	Gas Power	kW	12 - kcal/h 10.320 - BTU 40,944
Depth	Cm	70			
Height	Cm	90			
Net weight	Kg	110	Standard connection	V-Hz	.