Myriad V Residential LED - Housing only MYRDHS ST 2.7K PHDM SIL 2057957



Product features

The Myriad Housing 2700K Spot accent downlight is a high efficient 10W recessed spotlight, luminous flux: 1286lm, luminaire efficacy 129lm/W. Colour rendering index Ra>80, Colour temperature 2700K, Beam angle 28ø, Average life rated at 50,000Hrs L70B50, Protection rating IP20, Cut out dimensions:











PRODUCT OVERVIEW

IPC Code	2057957
Product name	MYRDHS ST 2.7K PHDM SIL
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Integral
General application	Museums & Galleries, Office, Retail, Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	1286
Luminaire efficacy (lm/W)	129
LOR (%)	100
Colour temperature (K)	2700
CRI (Ra)	85
Beam Angle (°)	28
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Average life (Nominal) (h)	50000
Housing colour	Silver Trim
IP rating	IP20
IK rating	IK02
Product EAN number	5025768579570
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data	
IPC Code	2057957
Product name	MYRDHS ST 2.7K PHDM SIL
Technology	LED
Housing	Aluminium




Myriad V Residential LED - Housing only MYRDHS ST 2.7K PHDM SIL 2057957


Mount	Ceiling recessed
Environment	Integral
General application	Museums & Galleries,Office,Retail,Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUNEW008
ETIM Class	EC001744
Optical data	
Fixture luminous flux (lm)	1286
Luminaire efficacy (Im/W)	129
LOR (%)	100
Colour temperature (K)	2700
CRI (Ra)	85
Adjustable chromaticity	N
Beam Angle (°)	28
Distribution type	Direct
Electrical data	
Total power consumption (W)	10
Mains voltage (V)	230-240V~
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Drive current (mA)	250
Lifetime data	
Average life (Nominal) (h)	50000
Disease to the second	
Physical data	
Housing colour	Silver Trim
IP rating	IP20
IK rating	IK02
Diffuser finish	Silver Trim
Reflector finish	Aluminium
Nominal Product Height (mm)	72
Weight (kg)	0.39
Recessed Depth (mm)	72
Packaging	
	Carton
Single packaging type Product EAN number	Carton 5025768579570
Packaging single length / height (cm)	17.5
Packaging single length / neight (cm) Packaging single width (cm)	17.5
Packaging single width (cm) Packaging single depth (cm)	17.5
DUN14 (outer)	05025768579570
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5
i donaging outer depth (em)	17.0



Myriad V Residential LED - Housing only MYRDHS ST 2.7K PHDM SIL 2057957

PHOTOMETRY





TECHNICAL DRAWINGS



Myriad V Residential LED - Housing only MYRDHS ST 2.7K PHDM SIL 2057957

