

## Myriad V Residential LED - Housing only

MYRDHS FL 2.7K PHDMEM SIL  
2057971



### Product features

- The Myriad Housing 2700K Flood accent downlight is a high efficient 12W recessed spotlight, luminous flux: 1167lm, luminaire efficacy 97lm/W. Colour rendering index Ra>80, Colour temperature 3000K, Beam angle 46°, Average life rated at 50,000Hrs L70B50, Protection rating IP20, Cut out dimensions: 76mm.



### PRODUCT OVERVIEW

IPC Code	2057971
Product name	MYRDHS FL 2.7K PHDMEM SIL
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Integral
General application	Museums & Galleries, Office, Retail, Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	1167
Luminaire efficacy (lm/W)	97
LOR (%)	100
Colour temperature (K)	2700
CRI (Ra)	85
Beam Angle (°)	46
Luminous flux (emergency) (lm)	307
Total power consumption (W)	12
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Average life (Nominal) (h)	50000
Housing colour	Silver Trim
IP rating	IP20
IK rating	IK02
Product EAN number	5025768579716
Lamps	Yes
Included lamp	INTEGRATED LED

### DATA TABLE

#### General data

IPC Code	2057971
Product name	MYRDHS FL 2.7K PHDMEM SIL

## Myriad V Residential LED - Housing only

*MYRDHS FL 2.7K PHDMEM SIL*  
2057971

Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Integral
General application	Museums & Galleries, Office, Retail, Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUNEW008
ETIM Class	EC001744

### Optical data

Fixture luminous flux (lm)	1167
Luminaire efficacy (lm/W)	97
LOR (%)	100
Colour temperature (K)	2700
CRI (Ra)	85
Adjustable chromaticity	N
Beam Angle (°)	46
Distribution type	Direct
Luminous flux (emergency) (lm)	307
Emergency duration (h)	3

### Electrical data

Total power consumption (W)	12
Mains voltage (V)	230-240V~
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Drive current (mA)	250
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Average life (Nominal) (h)	50000
----------------------------	-------

### Physical data

Housing colour	Silver Trim
IP rating	IP20
IK rating	IK02
Diffuser finish	Silver Trim
Reflector finish	Aluminium
Nominal Product Height (mm)	72
Weight (kg)	1.39
Recessed Depth (mm)	72

### Packaging





Single packaging type	Carton
Product EAN number	5025768579716
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5

## Myriad V Residential LED - Housing only


MYRDHS FL 2.7K PHDMEM SIL  
2057971

DUN14 (outer)	05025768579716
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5

### PHOTOMETRY





### TECHNICAL DRAWINGS




## Myriad V Residential LED - Housing only MYRDHS FL 2.7K PHDMEM SIL 2057971


**Concord** 2057971


 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

**Concord** 2057971  874/2012