

Myriad V Residential LED - Housing only

MYRDHS FL 2.7K PHDM WHT
2057993



Product features

- The Myriad Housing 2700K Flood accent downlight is a high efficient 10W recessed spotlight, luminous flux: 1167lm, luminaire efficacy 117lm/W. Colour rendering index Ra>80, Colour temperature 3000K, Beam angle 46°, Average life rated at 50,000Hrs L70B50, Protection rating IP20, Cut out dimensions: 76mm.



PRODUCT OVERVIEW

IPC Code	2057993
Product name	MYRDHS FL 2.7K PHDM WHT
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Integral
General application	Museums & Galleries, Office, Retail, Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	1167
Luminaire efficacy (lm/W)	117
LOR (%)	100
Colour temperature (K)	2700
CRI (Ra)	85
Beam Angle (°)	46
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Average life (Nominal) (h)	50000
Housing colour	White Trim
IP rating	IP20
IK rating	IK02
Product EAN number	5025768579938
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	2057993
Product name	MYRDHS FL 2.7K PHDM WHT
Technology	LED
Housing	Aluminium

Myriad V Residential LED - Housing only

MYRDHS FL 2.7K PHDM WHT
2057993

Mount	Ceiling recessed
Environment	Integral
General application	Museums & Galleries, Office, Retail, Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUNEW008
ETIM Class	EC001744

Optical data

Fixture luminous flux (lm)	1167
Luminaire efficacy (lm/W)	117
LOR (%)	100
Colour temperature (K)	2700
CRI (Ra)	85
Adjustable chromaticity	N
Beam Angle (°)	46
Distribution type	Direct

Electrical data

Total power consumption (W)	10
Mains voltage (V)	230-240V~
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Drive current (mA)	250
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	50000
-----------------------------------	-------

Physical data

Housing colour	White Trim
IP rating	IP20
IK rating	IK02
Diffuser finish	White Trim
Reflector finish	Aluminium
Nominal Product Height (mm)	72
Weight (kg)	0.39
Recessed Depth (mm)	72

Packaging


Single packaging type	Carton
Product EAN number	5025768579938
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5
DUN14 (outer)	05025768579938
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0

Myriad V Residential LED - Housing only MYRDHS FL 2.7K PHDM WHT 2057993

Packaging outer depth (cm)

17.5


PHOTOMETRY



Distance [m]	Cone diameter [m]	E _{0°} [lx]	E _{18.9°} [lx]	E _{37.5°} [lx]
0.5	0.34	9387	3861	3861
1.0	0.68	2272	965	965
1.5	1.03	1010	429	429
2.0	1.37	588	241	241
2.5	1.71	382	154	154
3.0	2.05	252	107	107

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 37.5°)


TECHNICAL DRAWINGS




Dimensions (mm)


Myriad V Residential LED - Housing only MYRDHS FL 2.7K PHDM WHT 2057993


Concord 2057993


 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

Concord 2057993  874/2012