

Skyline Street - Small

Skyline Street S 1-5klm NW WR35 I 9022

0066612



Product features

- The Skyline Street family is dedicated for road lighting applications. Light distribution: WR35 - Wide Road, color temperature: 4000K, total system power: 49W, total fixture output: 5748lm, luminaire efficacy: 117lm/W, LOR: 100%, colour rendering index: 70, LED Chromaticity: 5 step MacAdam ellipse tolerance, lifetime: 100000 hours at L90B50 @ 50°C, energy class: A++, A+, A, operating voltage: 220-240V / 50-60Hz, electronic driver, Without Controls, power factor: min. 0.9, electrical protection: Class I, Ingress protection rating: IP66, Impact resistance: IK08, dimensions: 525x255x105mm, weight: 6 kg, for 42-60mm side entry or post top installation with +/-15° adjustability, the housing is made of Die Cast Aluminium in RAL9022 color combined with tempered flat glass cover.



PRODUCT OVERVIEW

IPC Code	0066612
Product name	Skyline Street S 1-5klm NW WR35 I 9022
Technology	LED
Housing	LM6 Aluminium
Mount	Pole Fixed
Fixture rating	Enclosed
General application	Office,Hospitality,Retail,Logistics & Industry,Education,
Certifications	EUNEW029
ETIM Class	EC000062
Fixture luminous flux (lm)	5748
Luminaire efficacy (lm/W)	117
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	70
Photobiological Risk Group	RG1
Total power consumption (W)	49
Electrical protection	Class I
Control gear type	DALI
Dimmable	No
Housing colour	Grey (RAL 9022)
IP rating	IP66
IK rating	IK08
Product EAN number	5410288666129
Lamps	No

DATA TABLE

General data

IPC Code	0066612
Product name	Skyline Street S 1-5klm NW WR35 I 9022
Technology	LED
Housing	LM6 Aluminium
Mount	Pole Fixed

Skyline Street - Small

Skyline Street S 1-5klm NW WR35 I 9022

0066612

Fixture rating	Enclosed
General application	Office,Hospitality,Retail,Logistics & Industry,Education,
Certifications	EUNEW029
ETIM Class	EC000062

Optical data

Fixture luminous flux (lm)	5748
Luminaire efficacy (lm/W)	117
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	70
Distribution type	Wide Road WR35
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	49
Mains voltage (V)	220-240V~
Lamp power factor	0.99
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	9
Electrical protection	Class I
Control gear required	No
Control gear type	DALI
Dimmable	No
Drive current (mA)	620
Inrush Current (A)	6
Inrush Duration (µs)	800
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	11
Max. Luminaires per 13A C Breaker	14
Max. Luminaires per 16A C Breaker	18
Max. Luminaires per 20A C Breaker	22
Max. Luminaires per 10A B Breaker	6
Max. Luminaires per 13A B Breaker	8
Max. Luminaires per 16A B Breaker	11
Max. Luminaires per 20A B Breaker	13

Lifetime data

Lumen maintenance - L70 B50	100000
Lumen maintenance - L80 B50	100000
Lumen maintenance - L90 B50	100000

Physical data

Housing colour	Grey (RAL 9022)
IP rating	IP66
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Glass

Skyline Street - Small

Skyline Street S 1-5klm NW WR35 I 9022
0066612

Nominal Product Length (mm)	525
Nominal Product Width (mm)	255
Nominal Product Height (mm)	105
Weight (kg)	6.0
Wind Area (m ²)	0.034


Packaging

Single packaging type	Carton
Product EAN number	5410288666129
Packaging single length / height (cm)	52.5
Packaging single width (cm)	25.5
Packaging single depth (cm)	10.5
DUN14 (outer)	05410288666129
Units per outer package	1
Packaging outer length / height (cm)	52.5
Packaging outer width (cm)	25.5
Packaging outer depth (cm)	10.5


Safety data

Optimal operating condition (°C)	-40-50
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS





Skyline Street - Small

Skyline Street S 1-5klm NW WR35 I 9022


0066612


SYLVANIA 0066612


 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

SYLVANIA 0066612  874/2012