### Myriad V Residential LED - Housing only MYRDHS FL 3K PHDM BLK 2058021



#### **Product features**

The Myriad Housing 3000K Flood accent downlight is a high efficient 10W recessed spotlight, luminous flux: 1037lm, luminaire efficacy 104lm/W. Colour rendering index Ra>80, Colour temperature 3000K, Beam angle 46ø, Average life rated at 50,000Hrs L70B50, Protection rating IP20, Cut out dimensions: 76mm.











### PRODUCT OVERVIEW

IPC Code	2058021
Product name	MYRDHS FL 3K PHDM BLK
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Integral
General application	Hospitality,Office,Retail,Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	1037
Luminaire efficacy (Im/W)	104
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	85
Beam Angle (°)	46
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Average life (Nominal) (h)	50000
Housing colour	Black Trim
IP rating	IP20
IK rating	IK02
Product EAN number	5025768580217
Lamps	Yes
Included lamp	INTEGRATED LED

#### **DATA TABLE**

General data	
IPC Code	2058021
Product name	MYRDHS FL 3K PHDM BLK
Technology	LED
Housing	Aluminium



# Myriad V Residential LED - Housing only MYRDHS FL 3K PHDM BLK 2058021


Mount	Ceiling recessed
Environment	Integral
General application	Hospitality,Office,Retail,Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUNEW008
ETIM Class	
ETIM Class	EC001744
Optical data	
Fixture luminous flux (lm)	1037
Luminaire efficacy (lm/W)	104
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	85
Adjustable chromaticity	N
Beam Angle (°)	46
Distribution type	Direct
••	
Electrical data	
Total power consumption (W)	10
Mains voltage (V)	230-240V~
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Drive current (mA)	250
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	50000
. , , , ,	
Physical data	
Housing colour	Black Trim
IP rating	IP20
IK rating	IK02
Diffuser finish	Black Trim
Reflector finish	Aluminium
Nominal Product Height (mm)	72
Weight (kg)	0.39
Recessed Depth (mm)	72
Packaging	
Single packaging type	Carton
Product EAN number	5025768580217
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single width (cm)	17.5
DUN14 (outer)	05025768580217
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer length / height (cm) Packaging outer width (cm)	15.0
r ackaging outer width (CIII)	13.0


## Myriad V Residential LED - Housing only MYRDHS FL 3K PHDM BLK 2058021

Packaging outer depth (cm)

17.5

### **PHOTOMETRY**





#### **TECHNICAL DRAWINGS**



Page 3 of 4

## Myriad V Residential LED - Housing only MYRDHS FL 3K PHDM BLK 2058021

