Concord

Myriad V Residential LED - Housing only MYRDHS FL 3K DALI BLK 2058022



Product features

The Myriad Housing 3000K Flood accent downlight is a high efficient 10W recessed spotlight, luminous flux: 1037lm, luminaire efficacy 104lm/W. Colour rendering index Ra>80, Colour temperature 3000K, Beam angle 46ø, Average life rated at 50,000Hrs L70B50, Protection rating IP20, Cut out dimensions: 76mm.



PRODUCT OVERVIEW

| IPC Code | 2058022 |
|-----------------------------|--|
| Product name | MYRDHS FL 3K DALI BLK |
| Technology | LED |
| Housing | Aluminium |
| Mount | Ceiling recessed |
| Environment | Integral |
| General application | Hospitality,Office,Retail,Residential & Consumer |
| Certifications | EUNEW008 |
| ETIM Class | EC001744 |
| Fixture luminous flux (Im) | 1037 |
| Luminaire efficacy (Im/W) | 104 |
| LOR (%) | 100 |
| Colour temperature (K) | 3000 |
| CRI (Ra) | 85 |
| Beam Angle (°) | 46 |
| Total power consumption (W) | 10 |
| Electrical protection | Class II |
| Control gear type | Electronic |
| Minimum dimming level (%) | 1 |
| Average life (Nominal) (h) | 50000 |
| Housing colour | Black Trim |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5025768580224 |
| Lamps | Yes |
| Included lamp | INTEGRATED LED |
| | |

DATA TABLE

| General data | |
|--------------|-----------------------|
| IPC Code | 2058022 |
| Product name | MYRDHS FL 3K DALI BLK |
| Technology | LED |
| Housing | Aluminium |

Myriad V Residential LED - Housing only MYRDHS FL 3K DALI BLK 2058022

| Mount | Ceiling recessed |
|---------------------------------------|--|
| Environment | Integral |
| General application | Hospitality,Office,Retail,Residential & Consumer |
| Operating temperature rated (°C) | 25 |
| Certifications | EUNEW008 |
| ETIM Class | EC001744 |
| | |
| Optical data | |
| Fixture luminous flux (Im) | 1037 |
| Luminaire efficacy (Im/W) | 104 |
| LOR (%) | 100 |
| Colour temperature (K) | 3000 |
| CRI (Ra) | 85 |
| Adjustable chromaticity | Ν |
| Beam Angle (°) | 46 |
| Distribution type | Direct |
| | |
| Electrical data | |
| Total power consumption (W) | 10 |
| Mains voltage (V) | 230-240V~ |
| Electrical protection | Class II |
| Control gear type | Electronic |
| Minimum dimming level (%) | 1 |
| Drive current (mA) | 250 |
| Nominal Frequency (Hz) | 50/60Hz |
| | |
| Lifetime data | |
| Average life (Nominal) (h) | 50000 |
| | |
| Physical data | |
| Housing colour | Black Trim |
| IP rating | IP20 |
| IK rating | IK02 |
| Diffuser finish | Black Trim |
| Reflector finish | Aluminium |
| Nominal Product Height (mm) | 72 |
| Weight (kg) | 0.39 |
| Recessed Depth (mm) | 72 |
| | |
| Packaging | |
| Single packaging type | Carton |
| Product EAN number | 5025768580224 |
| Packaging single length / height (cm) | 17.5 |
| Packaging single width (cm) | 15.0 |
| Packaging single depth (cm) | 17.5 |
| DUN14 (outer) | 05025768580224 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 17.5 |
| Packaging outer width (cm) | 15.0 |
| | |




Myriad V Residential LED - Housing only MYRDHS FL 3K DALI BLK 2058022

Packaging outer depth (cm)

17.5

PHOTOMETRY



TECHNICAL DRAWINGS



Concord

Myriad V Residential LED - Housing only MYRDHS FL 3K DALI BLK 2058022

| Concord 2058022 | |
|---|-----------------------------------|
| This luminaire contains built in LED lamps. | |
| A ⁺⁺ A ⁺ A | |
| | |
| The lamps cannot be changed in the luminaire. | |
| 874/2012 | |
| This luminaire contains built in LED lamps. | A ⁺⁺ A ⁺ |

This luminaire contains built in LED lamps. The lamps cannot be changed in the luminaire. Concord 2058022 874/2012