

## ToLEDo T8 CCG and AC

ToLEDo T8 V4 3FT 12W 1400LM 830  
0027780



### Product features

- ToLEDo tube T8 V4 3ft, is 900mm LED T8 tube replacement for the 30W fluorescent tube. ToLEDo T8 V4 shares same glass tube construction design as traditional fluorescent T8 tubes and benefits from Omnidirectional 320° uniform light distribution. This tube is available with a CRI of 80 and in warm white, 3000K. High lumen package - 1400lm, lumen efficacy of 117 lm/W and A+ energy rating, dramatically reduce energy consumption and help to achieve quick payback on investment. Additionally, it has an impressive 200,000 switching cycles combined with 40,000 hours life span. Suitable for general illumination in offices, supermarkets, department stores, train stations, parking lots and maintenance free applications. ToLEDo T8 V4 comes with a 3-year warranty for complete peace-of-mind and compatible with electromagnetic gears and also suitable for direct mains operation.



## PRODUCT OVERVIEW

IPC Code	0027780
Product name	ToLEDo T8 V4 3FT 12W 1400LM 830
Technology	LED
Watt (Rated) (W)	12
Fixture rating	Open
General application	Hospitality,Logistics & Industry,Residential & Consumer
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740529
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Wattage (W)	12
Product Voltage (V)	230
Average life (Nominal) (h)	50000
Product EAN number	5410288277806

## DATA TABLE

### General data

IPC Code	0027780
Product name	ToLEDo T8 V4 3FT 12W 1400LM 830
Technology	LED
Watt (Rated) (W)	12
Fixture rating	Open
General application	Hospitality,Logistics & Industry,Residential & Consumer
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740529

### Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
----------------------------	---

## ToLEDo T8 CCG and AC

ToLEDo T8 V4 3FT 12W 1400LM 830  
0027780

Luminous flux (Rated) (lm)	1400
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	12
Starting time (max) (s)	1
Warm-up time to 60% of full light (max) (s)	1
Mains voltage (V)	220-240V~
Product Voltage (V)	230
Lamp power factor	0.9
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	12

### Lifetime data

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

### Physical data

Nominal Product Diameter (mm)	900
Weight (kg)	0.15

### Packaging

Single packaging type	Carton
Product EAN number	5410288277806
Packaging single length / height (cm)	91.0
Packaging single width (cm)	2.55
Packaging single depth (cm)	2.55
DUN14 (inner)	25410288277800
DUN14 (outer)	15410288277803
Units per outer package	10
Packaging outer length / height (cm)	99.0
Packaging outer width (cm)	21.0
Packaging outer depth (cm)	12.0

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

ToLEDo T8 CCG and AC  
ToLEDo T8 V4 3FT 12W 1400LM 830  
0027780

