

ToLEDo T8 CCG and AC TOLEDO T8 4FT 1600LM 865 20K 0028234

Product features

Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps. Omnidirectional 320° uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes. High lumen efficacy - 100 lm/W. Energy rating - A+. Switching cycles -100,000X. Average rated life 20,000 hours lifespan (L70 F50). Wide beam angle - 220°. High power factor - 0.50. Suitable for general illumination in offices, supermarkets, department stores, parking lots. Suitable for operation with electromagnetic gears and direct mains operation (220-240V). 2-Year warranty.



PRODUCT OVERVIEW

| IPC Code | 0028234 |
|----------------------------|--|
| Product name | TOLEDO T8 4FT 1600LM 865 20K |
| Technology | LED |
| Watt (Rated) (W) | 16 |
| Cap/Base | G13 |
| General application | Logistics & Industry, Education, Residential & Consumer, Office, |
| Certifications | EUERL010 |
| ETIM Class | EC001959 |
| Luminous flux (Im) | 1600 |
| Colour temperature (K) | 6500 |
| Light colour | Daylight |
| CRI (Ra) | 80 |
| Wattage (W) | 16 |
| Product Voltage (V) | 230 |
| Average life (Nominal) (h) | 20000 |
| Product EAN number | 5410288282343 |

DATA TABLE

| General data | | |
|----------------------------|--|--|
| IPC Code | 0028234 | |
| Product name | TOLEDO T8 4FT 1600LM 865 20K | |
| Technology | LED | |
| Watt (Rated) (W) | 16 | |
| Cap/Base | G13 | |
| General application | Logistics & Industry, Education, Residential & Consumer, Office, | |
| Certifications | EUERL010 | |
| ETIM Class | EC001959 | |
| Optical data | | |
| Luminous flux (Im) | 1600 | |
| Luminous flux (Rated) (Im) | 1600 | |
| Colour temperature (K) | 6500 | |
| Light colour | Daylight | |
| | | |



ToLEDo T8 CCG and AC TOLEDO T8 4FT 1600LM 865 20K 0028234

| CRI (Ra) | 80 |
|--|--|
| Lumen maintenance at end of nominal life (%) | 70 |
| Electrical data | |
| Wattage (W) | 16 |
| Starting time (max) (s) | 0.5 |
| Warm-up time to 60% of full light (max) (s) | 0.5 |
| Product Voltage (V) | 230 |
| Lamp power factor | 0.5 |
| No. Of switching cycles before premature failures | 50000 |
| Lamp Energy Label (class) | A+ |
| kWh per 1000 hours burning time | 16 |
| | |
| Lifetime data | |
| Average life (Nominal) (h) | 20000 |
| Average life (Rated) (h) | 20000 |
| Physical data | |
| Weight (kg) | 0.208 |
| | |
| Packaging | |
| Single packaging type | Carton |
| Product EAN number | 5410288282343 |
| Packaging single length / height (cm) | 125.5 |
| Packaging single width (cm) | 2.75 |
| Packaging single depth (cm) | 2.75 |
| DUN14 (outer) | 15410288282340 |
| Units per outer package | 10 |
| Packaging outer length / height (cm) | 129.7 |
| Packaging outer width (cm) | 22.6 |
| Packaging outer depth (cm) | 11.7 |
| Safety data | |
| Breakage cleaning instructions | Not applicable |
| Special purpose lamp | No |
| Suitable for household illumination | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |
| - | - |



ToLEDo T8 CCG and AC TOLEDO T8 4FT 1600LM 865 20K 0028234

| С ЕПЕ енергия • а | RG Υ ΙΙΑ ΙΕ ΙΑ ενεργεια |
|--|-------------------------------|
| SYLVANIA | 0028234 |
| A ⁺⁺ A ⁺ A | A ⁺ |
| C | |
| D E | |
| 16kW | h/1000h |