

Sylproof Tubular LED - DALI

Sylproof Tubular LED 2X1500 DALI WW
0047609



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



PRODUCT OVERVIEW

IPC Code	0047609
Product name	Sylproof Tubular LED 2X1500 DALI WW
Technology	LED
Housing	Acrylic/PMMA Tube
Mount	Surface
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Fixture luminous flux (lm)	5597
Luminous flux (lm)	5597
Luminaire efficacy (lm/W)	115.4
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	0
Total power consumption (W)	48.5
Electrical protection	Class I
Control gear type	Electronic dimmable
Minimum dimming level (%)	90
Average life (Nominal) (h)	50000
Housing colour	Matt Diffuser
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476094
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	0047609
Product name	Sylproof Tubular LED 2X1500 DALI WW

Sylproof Tubular LED - DALI

Sylproof Tubular LED 2X1500 DALI WW

0047609

Technology	LED
Housing	Acrylic/PMMA Tube
Mount	Surface
Environment	Interior
General application	Logistics & Industry
Operating temperature range (°C)	-20 to +25
ETIM Class	EC000109

Optical data

Fixture luminous flux (lm)	5597
Luminous flux (lm)	5597
Luminaire efficacy (lm/W)	115.4
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Distribution type	Direct
Photobiological Risk Group	0

Electrical data

Total power consumption (W)	48.5
Mains voltage (V)	220-240V~
Electrical protection	Class I
Control gear type	Electronic dimmable
Minimum dimming level (%)	90
Drive current (mA)	350
Glow Wire Test (°C)	650
Lamp Energy Label (class)	A+
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A C Breaker	24

Lifetime data

Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B10	49000
Lumen maintenance - L90 B50	35000
Average life (Nominal) (h)	50000

Physical data

Vertical Tilt (°)	360
Horizontal rotation (°)	360
Housing colour	Matt Diffuser
IP rating	IP66
IK rating	IK06
Diffuser finish	Matt/Opaque
Diffuser material	Acrylic/PMMA
Nominal Product Length (mm)	1600

Sylproof Tubular LED - DALI


Sylproof Tubular LED 2X1500 DALI WW
0047609

Nominal Product Width (mm)	112
Nominal Product Height (mm)	112
Weight (kg)	3.2

Packaging

Single packaging type	Carton
Product EAN number	5410288476094
Packaging single length / height (cm)	160.0
Packaging single width (cm)	13.0
Packaging single depth (cm)	13.0
DUN14 (outer)	05410288476094
Units per outer package	1
Packaging outer length / height (cm)	160.0
Packaging outer width (cm)	13.0
Packaging outer depth (cm)	13.0

PHOTOMETRY




Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [in]	Illuminance [lx]
0.5	1.16	0.5	1.97	6422
	2.19	1.0	3.94	886
1.0	2.32	1.0	3.94	1606
	4.39	2.0	7.87	224
1.5	3.48	1.5	5.90	714
	6.58	3.0	11.83	100
2.0	4.63	2.0	7.87	401
	6.78	3.0	11.83	88
2.5	5.79	2.5	9.84	237
	10.57	5.0	19.68	36
3.0	6.95	3.0	11.83	178
	13.17	6.0	23.66	26

Distance [m] Cone diameter [m] Illuminance [lx]


— C0 - C180 (Half beam angle: 131.0°)
— C90 - C270 (Half beam angle: 96.4°)


TECHNICAL DRAWINGS




Sylproof Tubular LED - DALI *Sylproof Tubular LED 2X1500 DALI WW* 0047609


SYLVANIA 0047609


 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

SYLVANIA 0047609  874/2012