

## Expospot 50 adjustable

EXPOSPOT 50 ADJUSTABLE RA80 3000K WB WHITE

0060215



### Product features

- Integrated LED adjustable accent downlight, single head, ideal for retail and display applications, die-cast aluminium body, passive cooling, beam angle: 51°, optics: aluminium reflector and lens combination, colour temperature: 3000K warm white, total system power: 13W, total fixture output: 1297lm, 100lm/W, LOR: 100%, colour rendering: Ra 80 typical, LED Chromacity: 3 step MacAdam ellipse, lifetime: 60,000 hours at 70% of the original output (L70B50), energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, electrical protection: CLASS II, ingress protection rating: IP20, suitable for internal environment only, ceiling cut-out: 110mm, outer dimensions: 121x103mm, weight: 0.52kg.



## PRODUCT OVERVIEW

IPC Code	0060215
Product name	EXPOSPOT 50 ADJUSTABLE RA80 3000K WB WHITE
Technology	LED
Housing	Aluminium
Mount	Recessed
Fixture rating	Enclosed
Environment	Internal
General application	Retail,
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	1297
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	51
Photobiological Risk Group	RG1
Total power consumption (W)	13
Electrical protection	Class II
Control gear type	Electronic
Control gear mounting	Remote
Dimmable	N
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5410288602158
Lamps	No
Included lamp	INTEGRATED LED

## Expospot 50 adjustable

*EXPOSPOT 50 ADJUSTABLE RA80 3000K WB WHITE*

0060215

### DATA TABLE

#### General data

IPC Code	0060215
Product name	EXPOSPOT 50 ADJUSTABLE RA80 3000K WB WHITE
Technology	LED
Housing	Aluminium
Mount	Recessed
Fixture rating	Enclosed
Environment	Internal
General application	Retail,
Certifications	EUNEW008
ETIM Class	EC001744

#### Optical data

Fixture luminous flux (lm)	1297
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	51
Photobiological Risk Group	RG1

#### Electrical data

Total power consumption (W)	13
Mains voltage (V)	230-240V~
Lamp power factor	0.83
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic
Control gear mounting	Remote
Dimmable	N
Drive current (mA)	300
Inrush Current (A)	17
Inrush Duration (µs)	199
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	38
Max. Luminaires per 13A C Breaker	50
Max. Luminaires per 16A C Breaker	61
Max. Luminaires per 20A C Breaker	78
Max. Luminaires per 10A B Breaker	23
Max. Luminaires per 13A B Breaker	30
Max. Luminaires per 16A B Breaker	37
Max. Luminaires per 20A B Breaker	47

## Expospot 50 adjustable

EXPOSPOT 50 ADJUSTABLE RA80 3000K WB WHITE  
0060215

### Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	60000
Lumen maintenance - L90 B20	60000
Lumen maintenance - L90 B10	55000



### Physical data

Housing colour	White
IP rating	IP20
IK rating	IK02
Reflector finish	Metallised
Nominal Product Width (mm)	121
Nominal Product Height (mm)	103
Weight (kg)	0.52
Recessed Depth (mm)	103

### Packaging


Single packaging type	Carton
Product EAN number	5410288602158
Packaging single length / height (cm)	18.0
Packaging single width (cm)	18.0
Packaging single depth (cm)	16.0
DUN14 (outer)	05410288602158
Units per outer package	1
Packaging outer length / height (cm)	18.0
Packaging outer width (cm)	18.0
Packaging outer depth (cm)	16.0

## PHOTOMETRY





## Expospot 50 adjustable EXPOSPOT 50 ADJUSTABLE RA80 3000K WB WHITE 0060215

### TECHNICAL DRAWINGS




**SYLVANIA** 0060215

 This luminaire contains built in LED lamps.

 } LED

The lamps cannot be changed in the luminaire.

874/2012 

## Expospot 50 adjustable

EXPOSPOT 50 ADJUSTABLE RA80 3000K WB WHITE

0060215

This luminaire contains built in LED lamps.

The lamps cannot be changed in the luminaire.

**SYLVANIA** 0060215 874/2012

A++  
A+  
A  
B  
C  
D  
E

LED