

Start Flat Panel LED ECO

START FLAT PANEL LED 3200LM 600 NW
0047401



Product features

- Edge lit LED flat panel low output. 40 W, Neutral White, 4000 K, 3200 lumens, 80 lm/W, 30000 hours lifetime (L70), PMMA opal diffuser, aluminium frame, steel body, electronic non dimmable driver. (HxWxD) 10.5 x 595 x 595 mm



PRODUCT OVERVIEW

IPC Code	0047401
Product name	START FLAT PANEL LED 3200LM 600 NW
Technology	LED
Housing	Powder coated steel
Mount	Ceiling recessed
Fixture rating	Enclosed
Environment	Internal
General application	Education, Hospitality, Office, Retail
Certifications	EUNEW008
ETIM Class	EC002892
E-number SE	7013616
Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	80
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Glare control	UGR <25
Photobiological Risk Group	Exempt Group 0
Total power consumption (W)	40
Electrical protection	Class II
Control gear type	Electronic
LED Flickering Rate	Ultra low (5% or less)
Average life (Nominal) (h)	30000
Housing colour	White
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288474014
Included lamp	INTEGRATED LED

Start Flat Panel LED ECO

START FLAT PANEL LED 3200LM 600 NW

0047401

DATA TABLE

General data

IPC Code	0047401
Product name	START FLAT PANEL LED 3200LM 600 NW
Technology	LED
Housing	Powder coated steel
Mount	Ceiling recessed
Fixture rating	Enclosed
Environment	Internal
General application	Education,Hospitality,Office,Retail
Operating temperature range (°C)	-10 to +40
Certifications	EUNEW008
ETIM Class	EC002892
E-number SE	7013616

Optical data

Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	80
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Beam Angle (°)	120
Distribution type	Direct
Glare control	UGR <25
Photobiological Risk Group	Exempt Group 0

Electrical data

Total power consumption (W)	40
Mains voltage (V)	220-240V~
Lamp power factor	0.9
Electrical protection	Class II
Control gear type	Electronic
Drive current (mA)	950
Inrush Current (A)	3
Inrush Duration (µs)	425
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)

Lifetime data

Lumen maintenance - L70 B50	30000
Average life (Nominal) (h)	30000

Start Flat Panel LED ECO

START FLAT PANEL LED 3200LM 600 NW
0047401


Physical data

Housing colour	White
IP rating	IP40/20
IK rating	IK03
Diffuser finish	Opal
Diffuser material	Acrylic PMMA
Reflector finish	Diffuser
Nominal Product Length (mm)	595
Nominal Product Width (mm)	595
Nominal Product Height (mm)	10.5
Weight (kg)	2.286
Recessed Depth (mm)	100

Packaging

Single packaging type	Carton
Product EAN number	5410288474014
Packaging single length / height (cm)	68.3
Packaging single width (cm)	62.8
Packaging single depth (cm)	3.5
DUN14 (outer)	15410288474011
Units per outer package	1
Packaging outer length / height (cm)	68.3
Packaging outer width (cm)	62.8
Packaging outer depth (cm)	3.5

PHOTOMETRY



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	1.51	E(0°) 481
	1.56	E(C90) 376
		E(C0) 352
1.0	3.02	E(0°) 115
	3.12	E(C90) 84
		E(C0) 88
1.5	4.53	E(0°) 496
	4.67	E(C90) 42
		E(C0) 39
2.0	6.04	E(0°) 279
	6.23	E(C90) 23
		E(C0) 22
2.5	7.55	E(0°) 178
	7.79	E(C90) 15
		E(C0) 14
3.0	9.07	E(0°) 124
	9.35	E(C90) 10
		E(C0) 10


Distance [m] Cone diameter [m] illuminance [lx]
 C0 - C180 (Half beam angle: 114.6°)
 C90 - C270 (Half beam angle: 113.0°)

TECHNICAL DRAWINGS


Start Flat Panel LED ECO


START FLAT PANEL LED 3200LM 600 NW

0047401




SYLVANIA 0047401

 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

Start Flat Panel LED ECO



START FLAT PANEL LED 3200LM 600 NW

0047401



This luminaire contains built in LED lamps.

The lamps cannot be changed in the luminaire.



SYLVANIA 0047401 874/2012