#### **Product features**

High-end architectural (4000K) neutral white LED pendant with non dimmable driver and remote gear housing, finished in a silver finish (RAL9006)

















#### PRODUCT OVERVIEW

IPC Code	2050692
Product name	MYRIAD PENDANT 4000K REMOTE EB SIL
Technology	LED
Mount	Ceiling pendant
Environment	Interior
General application	Hospitality,Office,Retail,Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001743
Fixture luminous flux (Im)	1093
Luminaire efficacy (lm/W)	109.3
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	80
Beam Angle (°)	30
Photobiological Risk Group	-
Total power consumption (W)	10
Electrical protection	Class II
Control gear mounting	Remote



Dimmable	No
Housing colour	Silver
IP rating	IP20
IK rating	IK02
Product EAN number	5025768506927
Included lamp	INTEGRATED LED

### **DATA TABLE**


General data	
IPC Code	2050692
Product name	MYRIAD PENDANT 4000K REMOTE EB SIL
Technology	LED
Mount	Ceiling pendant
Environment	Interior
General application	Hospitality,Office,Retail,Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001743
Optical data	
Fixture luminous flux (lm)	1093
Luminaire efficacy (lm/W)	109.3
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	80
Adjustable chromaticity	N
Beam Angle (°)	30
Distribution type	Direct symmetrical
Photobiological Risk Group	-
Electrical data	
Total power consumption (W)	10
Mains voltage (V)	220-240V~
Electrical protection	Class II
Control gear mounting	Remote
Dimmable	No
Drive current (mA)	250
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Lumen maintenance - L70 B50	50000
Physical data	
Housing colour	Silver
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	75
Nominal Product Width (mm)	75


Nominal Product Height (mm)	129
Nominal Product Diameter (mm)	75
Max. Lamp Diameter (mm) - D	75
Weight (kg)	0.45

#### Packaging

Single packaging type	Carton
Product EAN number	5025768506927
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5

### **PHOTOMETRY**





### **TECHNICAL DRAWINGS**

