

## Beacon LED Projector - Iris

Beacon LED Iris Projector O/B 3000K Three Circuit Track - Black  
2055969



### Product features

- Beacon Projector offers precision light exactly where it is needed. The Iris Projector has an adjusting lever to create a perfect circle of light in the required size. High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.



### PRODUCT OVERVIEW

IPC Code	2055969
Product name	Beacon LED Iris Projector O/B 3000K Three Circuit Track - Black
Technology	LED
Housing	Aluminium
Mount	Track Mounted
Fixture rating	Enclosed
General application	Museums & Galleries, Hospitality,
Certifications	EUNEW009
ETIM Class	EC001744
E-number FI	4260895
Fixture luminous flux (lm)	474
Luminaire efficacy (lm/W)	14
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	97
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG01
Total power consumption (W)	35
Product Voltage (V)	240
Electrical protection	Class II
Control gear type	Electronic dimmable 1-10V
Control gear mounting	Integral
Dimmable	Y
Housing colour	Black - RAL9005
IP rating	IP20
IK rating	IK02
Product EAN number	5025768551842
Lamps	No
Included lamp	INTEGRATED LED

### DATA TABLE

#### General data

IPC Code	2055969
Product name	Beacon LED Iris Projector O/B 3000K Three Circuit Track - Black

## Beacon LED Projector - Iris

*Beacon LED Iris Projector O/B 3000K Three Circuit Track - Black*  
2055969

Technology	LED
Housing	Aluminium
Mount	Track Mounted
Fixture rating	Enclosed
General application	Museums & Galleries, Hospitality,
Certifications	EUNEW009
ETIM Class	EC001744
E-number FI	4260895

### Optical data

Fixture luminous flux (lm)	474
Luminaire efficacy (lm/W)	14
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	97
Colour Variation Initial (SDCM)	3
Distribution type	Adjustable
Photobiological Risk Group	RG01

### Electrical data

Total power consumption (W)	35
Mains voltage (V)	230V~
Product Voltage (V)	240
Lamp power factor	0.95
Electrical protection	Class II
Control gear required	Yes
Control gear type	Electronic dimmable 1-10V
Control gear mounting	Integral
Dimmable	Y
Drive current (mA)	900
Inrush Current (A)	5
Inrush Duration (µs)	50
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	52
Max. Luminaires per 16A C Breaker	85

### Lifetime data

Lumen maintenance - L70 B50	72000
Lumen maintenance - L70 B20	72000
Lumen maintenance - L70 B10	72000
Lumen maintenance - L80 B50	72000
Lumen maintenance - L80 B20	72000
Lumen maintenance - L80 B10	72000
Lumen maintenance - L90 B50	45000
Lumen maintenance - L90 B20	36000
Lumen maintenance - L90 B10	33000

### Physical data

Housing colour	Black - RAL9005
----------------	-----------------

## Beacon LED Projector - Iris


*Beacon LED Iris Projector O/B 3000K Three Circuit Track - Black*  
**2055969**

IP rating	IP20
IK rating	IK02
Nominal Product Width (mm)	185
Nominal Product Height (mm)	215
Weight (kg)	1.365


### Packaging

Single packaging type	Carton
Product EAN number	5025768551842
Packaging single length / height (cm)	32.0
Packaging single width (cm)	15.5
Packaging single depth (cm)	13.0
DUN14 (outer)	05025768551842
Units per outer package	1
Packaging outer length / height (cm)	32.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	13.0

## PHOTOMETRY




## TECHNICAL DRAWINGS




## Beacon LED Projector - Iris


Beacon LED Iris Projector O/B 3000K Three Circuit Track - Black  
2055969


**Concord** 2055969


 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

**Concord** 2055969  874/2012