

Officelyte Classic LED

OFFLYTE CLASSIC LED HO 4K DALI EM

2058063



Product features

- Concord OfficeLyte Classic LED HO 4K DALI EM is a high performance low glare luminaire for offices and education applications. Ceiling recessed 600x600mm. Micro Prismatic optics. White RAL 9010. DALI Dimmable, Emergency 3 hours maintained. 4000K Neutral White LED, CRI >85, chromaticity tolerance of 3-step MacAdam ellipse, lumen package of 3,750lm, total power consumption 51W, efficacy of 74lm/W . Lumen maintenance of L70B50 at 50,000 hours, UGR<19. IK02, IP40, Electrical Protection Class II. Polycarbonate diffuser, Glow Wire test 850°C.



PRODUCT OVERVIEW

IPC Code	2058063
Product name	OFFLYTE CLASSIC LED HO 4K DALI EM
Technology	LED
Housing	Zintec Steel
Mount	Ceiling recessed
General application	Office,Hospitality,Retail,Education,
Certifications	EUNEW001
ETIM Class	EC002892
Fixture luminous flux (lm)	3750 (EM=182)
Luminaire efficacy (lm/W)	74
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	UGR<19
Photobiological Risk Group	0
Total power consumption (W)	51
Electrical protection	Class II
Control gear type	External
Minimum dimming level (%)	99
Average life (Nominal) (h)	50000
Housing colour	White RAL 9010
IP rating	IP40
IK rating	IK02
Product EAN number	5025768580637
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	2058063
----------	---------

Officelyte Classic LED

OFFLYTE CLASSIC LED HO 4K DALI EM

2058063

Product name	OFFLYTE CLASSIC LED HO 4K DALI EM
Technology	LED
Housing	Zintec Steel
Mount	Ceiling recessed
General application	Office,Hospitality,Retail,Education,
Certifications	EUNEW001
ETIM Class	EC002892

Optical data

Fixture luminous flux (lm)	3750 (EM=182)
Luminaire efficacy (lm/W)	74
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Distribution type	Direct
Glare control	UGR<19
Photobiological Risk Group	0
Emergency duration (h)	3

Electrical data

Total power consumption (W)	51
Mains voltage (V)	220-240V~
Mains frequency (Hz)	50
Electrical protection	Class II
Control gear type	External
Minimum dimming level (%)	99
Drive current (mA)	1400
Inrush Current (A)	45
Inrush Duration (µs)	20
Glow Wire Test (°C)	850
Lamp Energy Label (class)	A++
Max. Luminaires per 16A C Breaker	50

Lifetime data

Average life (Nominal) (h)	50000
----------------------------	-------

Physical data

Housing colour	White RAL 9010
IP rating	IP40
IK rating	IK02
Diffuser finish	Satin
Diffuser material	Acrylic
Reflector finish	Micro Prismatic
Nominal Product Length (mm)	595
Nominal Product Width (mm)	595
Nominal Product Height (mm)	95
Weight (kg)	7.8

Officelyte Classic LED OFFLYTE CLASSIC LED HO 4K DALI EM 2058063

Recessed Depth (mm)	90
---------------------	----




Packaging

Single packaging type	Carton
Product EAN number	5025768580637
Packaging single length / height (cm)	62.0
Packaging single width (cm)	62.0
Packaging single depth (cm)	17.0
DUN14 (outer)	05025768580637
Units per outer package	1
Packaging outer length / height (cm)	62.0
Packaging outer width (cm)	62.0
Packaging outer depth (cm)	17.0

Safety data


Compatible dimmers	DALI
--------------------	------

PHOTOMETRY





TECHNICAL DRAWINGS

Officelyte Classic LED OFFFLYTE CLASSIC LED HO 4K DALI EM 2058063




Concord 2058063

 This luminaire is compatible with bulbs of the energy classes:



This luminaire is sold with a bulb of the energy class:

874/2012 

Officelyte Classic LED OFFLYTE CLASSIC LED HO 4K DALI EM 2058063

This luminaire is compatible with bulbs of the energy classes:

This luminaire is sold with a bulb of the energy class:

Concord 2058063 874/2012

Energy efficiency scale: A++, A+, A, B, C, D, E. A++ to A are marked as LED compatible. B to E are crossed out.