

## ToLEDO Mirage G120

TOLEDO MIRAGE G120  
0029908



### Product features

- A perfect choice for hospitality, decorative and mood lighting applications Unique and innovative lamp design and construction Low-lumen output to create the low-lit effect and gives no glare Low power construction: only 2.5W Perfect for SylPendant fixtures - a range of unique and elegant E27 lamp pendants, available in copper, brass, black and white finish Candlelight 2000K colour temperature creates a warm and cosy ambience High colour rendering - CRI80 High quality, scratch and temperature resistant golden tinted glass envelope 25,000 hours of average rated life. Last 25 times longer than incandescent lamps Omni-directional light distribution of 300° Non-dimmable More than 100,000X switching cycles 3 years warranty



### PRODUCT OVERVIEW

IPC Code	0029908
Product name	TOLEDO MIRAGE G120
Technology	LED
Watt (Rated) (W)	2.5
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740678
Luminous flux (lm)	125
Colour temperature (K)	2000
Light colour	Candlelight
CRI (Ra)	80
Wattage (W)	2.5
Product Voltage (V)	230
Average life (Nominal) (h)	25000
Product EAN number	5410288299082

### DATA TABLE

#### General data

IPC Code	0029908
Product name	TOLEDO MIRAGE G120
Technology	LED
Watt (Rated) (W)	2.5
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740678

## ToLEDO Mirage G120

TOLEDO MIRAGE G120  
0029908

### Optical data

Luminous flux (lm)	125
Luminous flux (Rated) (lm)	125
Colour temperature (K)	2000
Light colour	Candlelight
CRI (Ra)	80
Beam angle (Rated) (°)	100

### Electrical data

Wattage (W)	2.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	100000
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

### Physical data

Nominal Product Length (mm)	165
Nominal Product Diameter (mm)	125
Weight (kg)	0.14

### Packaging

Single packaging type	Carton
Product EAN number	5410288299082
Packaging single length / height (cm)	17.8
Packaging single width (cm)	13.2
Packaging single depth (cm)	13.2
DUN14 (outer)	15410288299089
Units per outer package	4
Packaging outer length / height (cm)	28.0
Packaging outer width (cm)	28.0
Packaging outer depth (cm)	20.5

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

ToLEDO Mirage G120  
TOLEDO MIRAGE G120  
0029908

