


ToLEDo Vintage G95 DIMMABLE

TOLEDO™ VINTAGE G95 DIM 250LM 820 E27 SL
0028006



Product features

- New and innovative Flexible Filament Chip Technology (FFCT) designed to create the low-lit vintage effect.
- Perfect for hotels, restaurants, heritage lighting, bars and decorative applications.
- The ideal LED solution to replace incandescent vintage globe lamps.
- Low glare - suitable for low height installation.
- 2000K colour temperature, to create a cosy ambience.
- Golden tinted glass envelope.
- 15,000 hours average rated life. Last 7.5 times longer than incandescent vintage lamps.
- Unique filament construction design - 'Helix' shape.
- Omni-directional light distribution - 300°.
- Low-lumen output to create low-lit effect - 250lm.
- More than 100,000X switching cycles.
- 3 years warranty.
- Environment friendly - no mercury and lower CO2 emissions.
- Dimmable on approved dimmers.



PRODUCT OVERVIEW

IPC Code	0028006
Product name	TOLEDO™ VINTAGE G95 DIM 250LM 820 E27 SL
Technology	LED
Watt (Rated) (W)	5.5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer,
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740576
Luminous flux (lm)	250
Colour temperature (K)	2000
Light colour	Candlelight
CRI (Ra)	80
Wattage (W)	5.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288280066

DATA TABLE

General data

IPC Code	0028006
Product name	TOLEDO™ VINTAGE G95 DIM 250LM 820 E27 SL
Technology	LED
Watt (Rated) (W)	5.5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer,
Operating temperature rated (°C)	25
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740576

ToLEDo Vintage G95 DIMMABLE

TOLEDO™ VINTAGE G95 DIM 250LM 820 E27 SL
0028006

Optical data

Luminous flux (lm)	250
Luminous flux (Rated) (lm)	250
Colour temperature (K)	2000
Light colour	Candlelight
Colour Code	820
CRI (Ra)	80
Beam angle (Rated) (°)	360

Electrical data

Wattage (W)	5.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.8
No. Of switching cycles before premature failures	20000
Lamp Energy Label (class)	A
kWh per 1000 hours burning time	6
Nominal Frequency (Hz)	50Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	140
Nominal Product Diameter (mm)	95
Weight (kg)	0.055

Packaging

Single packaging type	Carton
Product EAN number	5410288280066
Packaging single length / height (cm)	15.8
Packaging single width (cm)	10.0
Packaging single depth (cm)	10.0
DUN14 (inner)	25410288280060
Units per inner package	6
Packaging inner length / height (cm)	62.3
Packaging inner width (cm)	10.5
Packaging inner depth (cm)	16.8
DUN14 (outer)	15410288280063
Units per outer package	60
Packaging outer length / height (cm)	63.8
Packaging outer width (cm)	55.5
Packaging outer depth (cm)	36.2

Safety data

ToLEDo Vintage G95 DIMMABLE

TOLEDO™ VINTAGE G95 DIM 250LM 820 E27 SL

0028006

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures
Safety message	Dimmable with approved dimmers

