

ToLEDo Retro Ball ToLEDo RT Ball V3 ST 470LM 827 E14 BL 0027256



Product features

• Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps • The versatile ToLEDo Retro Ball range is the ideal replacement for incandescent lamps and perfect for chandeliers and decorative applications. • Same look, size and functionality as incandescent lamps. • Omni-directional light distribution. • A++ energy rating - up to 100 lm/W. • Suitable for replacement of 35W incandescent lamps. • Gives same sparkling light effect as incandescent lamp. • 88% energy saving. • Dimensionally identical to incandescent lamps - fits all fixtures • Environment friendly - no mercury and lower CO2 emissions. • Color temperature - 2700K









PRODUCT OVERVIEW

IPC Code	0027256
Product name	ToLEDo RT Ball V3 ST 470LM 827 E14 BL
Technology	LED
Watt (Rated) (W)	4.5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number SE	8295056
Luminous flux (Im)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	300
Wattage (W)	4.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288272566
Chromaticity coordinate Y	-1

DATA TABLE

General data	
IPC Code	0027256
Product name	ToLEDo RT Ball V3 ST 470LM 827 E14 BL
Technology	LED
Watt (Rated) (W)	4.5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality,Residential & Consumer
Operating temperature rated (°C)	25



ToLEDo Retro Ball ToLEDo RT Ball V3 ST 470LM 827 E14 BL 0027256

Certifications	EUTIE103
ETIM Class	EC001959
E-number SE	8295056
Optical data	
Luminous flux (lm)	470
Luminous flux (Rated) (Im)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Beam Angle (°)	300
Beam angle (Rated) (°)	300
Lumen maintenance at end of nominal	70
life (%)	
Clastrian data	
Electrical data	45
Wattage (W)	4.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	5
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Nothinal) (II) Average life (Rated) (h)	15000
, trolago mo (riatoa) (m)	10000
Physical data	
Nominal Product Length (mm)	80
Nominal Product Diameter (mm)	45
Weight (kg)	0.019
Packaging	
• •	Mix blictor/200/ corton 200/ pl
Single packaging type Product EAN number	Mix blister(20% carton, 80% pl
Packaging single length / height (cm)	5410288272566 15.2
Packaging single length / neight (cm) Packaging single width (cm)	13.1
Packaging single width (cm) Packaging single depth (cm)	4.6
DUN14 (inner)	25410288272560
Units per inner package	6
Packaging inner length / height (cm)	28.5
Packaging inner width (cm)	15.1
r achauliu iiiici wiuli (CIII)	10.1



ToLEDo Retro Ball ToLEDo RT Ball V3 ST 470LM 827 E14 BL 0027256

Packaging inner depth (cm)	16.1
DUN14 (outer)	15410288272563
Units per outer package	60
Packaging outer length / height (cm)	84.4
Packaging outer width (cm)	30.4
Packaging outer depth (cm)	32.7

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Suitable for accent lighting	Yes
Safety message	Not Suitable for totally enclosed fixtures

