

ToLEDo G4

ToLEDo G4 200LM 827 SL
0026514



Product features

- LED retrofit replacement for halogen low voltage capsules • Compact design • 300° omni-directional light distribution • Low voltage: 12V AC/DC • 200lm = 21W halogen G4 lamp • High lumen efficacy: 91lm/W • 90% energy saving • A++ energy rating • Non-dimmable • Suitable for chandeliers, interior display, shop windows, decorative and general lighting applications



PRODUCT OVERVIEW

IPC Code	0026514
Product name	ToLEDo G4 200LM 827 SL
Technology	LED
Watt (Rated) (W)	2.2
Fixture rating	Open
General application	Hospitality,Retail,Residential & Consumer,Museums & Galleries,
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740621
Luminous flux (lm)	200
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	300
Wattage (W)	2.2
Product Voltage (V)	12
Average life (Nominal) (h)	15000
Product EAN number	5410288265148

DATA TABLE

General data

IPC Code	0026514
Product name	ToLEDo G4 200LM 827 SL
Technology	LED
Watt (Rated) (W)	2.2
Fixture rating	Open
General application	Hospitality,Retail,Residential & Consumer,Museums & Galleries,
Operating temperature rated (°C)	25
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740621

ToLEDo G4

ToLEDo G4 200LM 827 SL

0026514

Optical data

Luminous flux (lm)	200
Luminous flux (Rated) (lm)	200
Colour temperature (K)	2700
Light colour	Homelight
Colour Code	827
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	300
Beam angle (Rated) (°)	300
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	2.2
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<1
Product Voltage (V)	12
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	DC/50/60Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	45
Nominal Product Diameter (mm)	16
Weight (kg)	0.008

Packaging

Single packaging type	Carton
Product EAN number	5410288265148
Packaging single length / height (cm)	5.2
Packaging single width (cm)	4.8
Packaging single depth (cm)	4.8
DUN14 (inner)	25410288265142
Units per inner package	10
Packaging inner length / height (cm)	25.5
Packaging inner width (cm)	10.5
Packaging inner depth (cm)	7.2
DUN14 (outer)	15410288265145
Units per outer package	100

ToLEDo G4

ToLEDo G4 200LM 827 SL

0026514

Packaging outer length / height (cm)	55.0
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	17.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Suitable for approved transf./dimmers
Safety message	Not Suitable for totally enclosed fixtures

