

**INCREASED
PRODUCTIVITY**

ELITE 1 - ELITE 2

INTERIOR FILLER SYSTEM POWDER

ELITE 1

- ▶ HIGH FILLING POWER
- ▶ UP TO 5 MM PER COAT
- ▶ SUPERIOR EFFICIENCY

ELITE 2

- ▶ EXCELLENT SPREADING
- ▶ EXTRA FINE AND WHITE



PURPOSE

Surface filler system in powder, interior use, manual application.

SUBSTRATES

ELITE 1 – ELITE 2 can be applied on:

- Concrete
- Cement
- Old painted surfaces
- Gypsum plaster
- Plasterboards
- Primed wood or plywood
- Dry wall lining

OVERCOATING

ELITE 1 – ELITE 2 can be painted over with any kind of paint or coating.

Physical and technical FEATURES

ELITE 1 – ELITE 2: fillers in powder form for interior use, made of selected quarry materials and cellulose binder.

- Characterization (NFT 36-005): Family III-Class 2
- Codification (EN 16566): G₃S₀V₀W₀A₀C₀R₀
- Application thickness: ELITE 1: Up to 5 mm/coat
ELITE 2: Up to 1 mm/coat
- Consumption (in thin layer): ELITE 1: 300 to 400 g/m² related to substrate condition
ELITE 2: 200 to 250 g/m² related to substrate condition
- Working time : 10 hours
- Overcoat: When fully dry
- Colour: ELITE 1: Off white – ELITE 2: White
- Adhesion filler/substrate (EN 16 566): > 0.5 Mpa

USE AND STORAGE CONDITIONS

- Application tool : with trowel, surfacing blade or spraying machine (empty the spraying equipment after daily use).
- Tools cleaning: with water
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored in dry conditions.

PACKAGING

- Bags of 25 kg

RECOMMENDATIONS and care for use

- Do not apply under a temperature < 8 °C and > 35 °C nor under an hygrometry rate over 70%.
- Do not apply on overheated surfaces
- Do not apply on damp substrates
- Do not apply on polystyrene, nor on wall paper, nor on exterior substrates.

SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- EN 16566: Coating Fillers for interior and/or exterior works.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 59.4 (NFP 74-204): wall papers and wall coverings processing

HEALTH AND SAFETY

- No danger tag.
- Very low VOC emissions : < 0,01 %.
- Safety data sheets available on www.toupretpro.co.uk or toupret.com.

The data sheet information, especially the guidelines relevant to the application and final use of **ELITE 1 - ELITE 2** are provided in good faith and result from the knowledge of the products and experience of TOUPRET Company. The product is required to be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions



Information on the level of emission of volatile substances in indoor air, presenting a risk of inhalation toxicity, on a class scale from A + (very low emissions) to C (high emissions).